



# ASM 306 S

## ASM 306 S

- Highest reliability and accuracy for full-time testing operation
- Fast, repeatable and high sensitivity measurements
- Compact unit with intuitive menu for easy operation
- Compact unit with large and high resolution touch screen
- Probe and calibrated leak to be ordered separately

Technical Data	ASM 306 S
Backing pump	with oil free backing pump
Dimensions (L x W x H)	350 x 305 x 421 mm   13.78 x 12.01 x 16.57 inch
I/O interfaces	Basic 15 pins I/O
Minimum detectable leakage rate for helium (sniffing leak detection)	1 · 10 <sup>-8</sup> Pa m <sup>3</sup> /s   7.5 · 10 <sup>-8</sup> Torr l/s   1 · 10 <sup>-7</sup> mbar l/s
Power consumption max.	300 VA
Response time	1 s
Sound pressure level	55 dB(A)
Start-up time (20°C) without calibration	2 min
Supply	100 – 240 V, 50/60 Hz
Test method	Sniffing leak detection
User interface	High resolution graphic color touch screen (detachable)
Weight	22 kg   48.5 lb

Order number	
ASM 306 S	RSAS00A0MM9A

Accessories	
<b>Calibration Sniffing calibration</b>	
Calibrated leak for ASM306 S, 100% Hydrogen, leak rate between 4 and 6 · 10 <sup>-5</sup> mbar l/s	127387
Calibrated leak for ASM306 S, 100% Helium, leak rate between 4 and 6 · 10 <sup>-5</sup> mbar l/s	127388
<b>Sniffing/Spraying Sniffer probes</b>	
High flow sniffer probe for ASM 306 S, 2 m hybrid cable length, rigid nozzle	PRB2H02HA
High flow sniffer probe for ASM 306 S, 5 m hybrid cable length, rigid nozzle	PRB2H05HA
High flow sniffer probe for ASM 306 S, 10 m hybrid cable length, rigid nozzle	PRB2H10HA
<b>Transport Transportation accessories</b>	
Trolley with two wheels	114820

## **VACUUM SOLUTIONS FROM A SINGLE SOURCE**

Pfeiffer Vacuum stands for innovative and custom vacuum solutions worldwide, technological perfection, competent advice and reliable service.

## **COMPLETE RANGE OF PRODUCTS**

From a single component to complex systems:

We are the only supplier of vacuum technology that provides a complete product portfolio.

## **COMPETENCE IN THEORY AND PRACTICE**

Benefit from our know-how and our portfolio of training opportunities!

We support you with your plant layout and provide first-class on-site service worldwide.

Are you looking for a  
perfect vacuum solution?  
Please contact us:

**Pfeiffer Vacuum GmbH**  
Headquarters · Germany  
T +49 6441 802-0  
info@pfeiffer-vacuum.de

[www.pfeiffer-vacuum.com](http://www.pfeiffer-vacuum.com)

All data subject to change without prior notice.

**PFEIFFER**  **VACUUM**